

- Drafts
- Pending
- Active
- Failed
- Saved
- S2: (4394) on near9 off
- S3: (4394) S2
- S4: (4) S1 near9 S2
- S1: (47910) port near9 power
- S5: (4691) switch\$5 near9 S1
- S6: (611) supply\$5 near9 port near9 power near9 S5
- S8: (24) program\$4 near9 S7
- S7: (1251) port near9 power near9 mode
- S9: (33238) power near5 port
- S10: (95834) user near9 mode
- S11: (10) S9 near9 S10
- S12: (156472) select\$5 near9 (port pin)
- S13: (4766) nonpower\$3 non-power\$3
- S17: (1) on near9 off near9 S9
- S20: (1931045) mode same11
- S23: (4348) S9 same off same off
- S24: (3763553) S9 sameonsame off
- S25: (35) S9 same on same off
- S14: (5) S12 near9 S13
- S15: (89) S13 near9 (port pin)
- S16: (1) configur\$4 near9 S9 near9 S10
- S18: (90) on near9 off near9 port
- S19: (831) power same port same on same off
- S21: (35) mode same S19
- S22: (5) power near20 port near20 on near20 off
- S26: (1) ("5552991").PN.
- S28: (47942) port near9 power
- S29: (15) S27 with S28
- S27: (33999) ring near9 detect\$3
- Favorites
- Tagged (1)
- UDC
- Queue
- Trash

10/1996, 310

Search

Blanks Highlight all hit terms initially

DBs: US, PGPUB, USPAT, USOOR, PPRS, EPO, JPO, DERWENT, IBM_TDB

Default operator: **OR**

S27 with S28

U	Document ID	Issue Date	Pages	Title	Current OR	Current XRef	Retrieval Cls	Inventor	S	C	P	2	3	4
	US 200005084262 2000/05/21	19		Protected bidirectional wdm nc 398/10				Obara, Masaru et al.	<input checked="" type="checkbox"/>	<input type="checkbox"/>				

Hits Details HTML

Ready

NUM